
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☐ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☒ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Stretchcoat Inc.
Product Name: Airlessco Pump Conditioner

Using Airlessco Pump Conditioner:

Airlessco pump conditioner is intended to prevent rust corrosion between normal uses of your airless spray equipment. For long-term storage of an airless pump, use a 50/50 mixture of mineral spirits and motor oil. Always make sure there is no pressure in the unit, and close the prime/pressure

relief valve for storage. After long-term storage flush with soapy water and then perform a clean water flush if you will be painting with water-base paint. If using oil-base paint, flush out the mineral spirits/oil mixture with the material to be sprayed.

Airlessco Pump Conditioner MATERIAL SAFETY DATA SHEET

SECTION 1

MANUFACTURER: Stretchco ADDRESS: 11703 E. Washington Blvd., Whittier, CA 90606

EMERGENCY TELEPHONE NUMBER: (213) 696-1370

SALES NAME: Airlessco Pump Conditioner CHEMICAL NAME: Cleaning compound, proprietary

SECTION 2: PHYSICAL DATA

APPEARANCE & ODOR: Liquid, blue, odorless

SPECIFIC GRAVITY: 9.5-9.7

SOLUBILITY IN WATER: Completely

VAPOR PRESSURE: N/A

EVAPORATION RATE: N/A

SOLIDS CONTENT: .086%

BOILING POINT: N/A

VAPOR DENSITY: N/A

SECTION 3: FIRE AND EXPLOSION HAZARD DATA

N/A

SECTION 4: REACTIVITY DATA

STABILITY: Stable

SECTION 5: SPILL OR LEAK PROCEDURES

SPILLAGE: Flush with water

SECTION 6: HEALTH HAZARD DATA

EYE CONTACT: Can be irritating to eyes. Contains sodium metasilicate.

SKIN CONTACT: Can be slightly irritating to skin.

INHALATION: Non-Corrosive. Spray can be an irritant.

FIRST AID: Procedures; Eye Contact - Wash with water at least 15 minutes and get medical attention. Skin Contact - Wash affected area with soap and water. If irritation persists get medical attention.

INHALATION: Move person to fresh air.

ANTIDOTE: If swallowed, give large amounts of water. Call Physician.

SECTION 7: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Maintain good ventilation, no equipment required.

GLOVES: Rubber

EYE PROTECTION: Goggles or face shield.